

Pre-Fresh Spa and Pool Filling Filter
TECHNICAL DATA

www.SpaDepot.com

PreFresh™



Physical:

2.5"D x 10.75"L

1.35 lbs.

Standard U.S. Garden hose fittings

Composition:

Oxidation/reduction catalyst media and Granular Activated Carbon with pre-screen and micro-pore pad filters.

Operation:

Capacity: 8,000 gallons*

Flow Rate: 2.5 GPM

Temperature Range: 35° - 100°F

Working Pressure: 20-100 PSI

*varies with quality of source water

Contaminant Mitigation:

Mercury
Lead
Iron
Copper
Cadmium
Barium
Chromium VI
Chromium III
Selenium
Volatile organic contaminants (VOC)
Pesticide residues
Suspended solids
Organics
Lime scale
Spores
Hydrogen sulfide
Chloramines
Chlorine dioxide
Phosphates
Fluoride
Nitrates
Arsenic
Rust (iron oxide)
Endrin
Lindane
Methoxychlor
Toxaphene
Silvex

Operation:

Flush unit with water for 30 seconds prior to each use. Replace end caps after use. Protect from freezing.

Specifications subject to change without notice. No warranty of suitability for any purpose other than the filtration of spa or pool fill water from a potable water source is expressed or implied.